


AMATRON UL LED CORN COB LIGHTING



B : o (m c (R R Q R R R



G : o (m c (R R Q R R R



@ : : o (m c (R R Q R R R

ÆTÆVÛUPÁWŠÁŠÖÖÁÔ[!}ÁÔ[àÁæ {]•Á
|[, ^!Á^}^!•^Á& [•c•Áà ^ÁæcÁ|^æ•cÁÍ Í ÁÁ
& [{]æ!^áÁc [Á& []ç^}cá []æ|Á@á*•Áá}c^}•æc^Á
|á*•cá}•ÉÁÔ[!}ÁÔ[àÁá~|à•Áá~!}Áç!^Áá!á*•c|~Á
æ}áÁáá•]•!•^Á|á*•cÁ [ç^!ÁæÁHÍÉÁá^*!•^Á
|æ}•^É

- W N - E O N N - p R - p R E W æ!^Áá^æ!Á
æ•Á@á*•Ááæ~Á|æ {]•Áá}Áæ!•^Áæ!^æ•Áá}Á
, æ!^@ [~•^•ÉÁ-æ&c [|á•ÉÁæ}áá*æ!æ*•^•É

Ô[!}ÁÔ[àÁá~|à•Áæ!^Á { æá^Áá}Á { ^áá~ { Áæ}áÁ
{ [*~|Ááæ•^•Áæ}áÁ•&!^ , Ááá!^&c|^Áá}c [Á!^*~|æ!Á
|á*•cÁ-áçc~!^•É

V@^•^Á@á*•Áá}c^}•æc^ÁŠÖÖ•Á^ { æcÁ} [Á@^æcÁæ}áÁ
\\^]ÁçEÖÁ& [•c•Áá [,]ÉÁV@^á!Á [] *Á|á-^Á!^á~&^Á
{ æá}c^}æ}&^Á& [•c•Áá}Á@æ!áÉc [É!^æ&@Áæ!^æ•Á
æ}áÁá [Á] [cÁ!^~~á!^Ááæ||æ•c•É

V@^•^Á|á*•c•Áæ!^Áæçæ!æ!^Á- [!Áà [c@Á
& []•~ { ^!•Áæ}áÁ& [{ { ^!&æ|Áá~^!•É

- Energy Efficient
- High Intensity
- Long Lasting
- Instant On/Off to Full Brightness
- No Flickering
- Zero Warm-up time

FEATURES

- Instant On/Off. No flickering or cold start issues.
- Longer life reduces maintenance costs in hard to reach areas.
- Eco friendly. Contains no mercury or lead.
- Energy efficient. Uses 70-90% less energy than traditional HID and CFL lights.
- No heat from light source. Requires less air conditioning.
- High CRI with great directionality.

MODELS

Model No.	Power	Voltage	Chips	Kelvin	Lumens	Dia X Length
AM-15WSMD	15W	85-265VAC	216	2700-6700K	1800 lm	2.9" x 6.3" (73mm x 150mm)
AM-20WSMD	20W	85-265VAC	312	2700-6700K	2400 lm	2.9" x 7.3" (73mm x 160mm)
AM-30WSMD	30W	100-300VAC	486	2700-6700K	4060 lm	3.5" x 8.6" (90mm x 218mm)
AM-40WSMD	40W	100-300VAC	660	2700-6700K	5520 lm	3.5" x 10.2" (90mm x 258mm)
AM-50WSMD	50W	100-300VAC	780	2700-6700K	6280 lm	3.5" x 10.2" (90mm x 258mm)
AM-60WSMD	60W	100-300VAC	900	2700-6700K	7200 lm	3.5" x 10.9" (90mm x 278mm)

SPECS

BASE	E26 OR E39
BEAM ANGLE	360 DEGREES
FREQUENCY RANGE	50-60Hz
OPERATING TEMP	-40 DEGREES - 113 DEGREES F
RATING	IP40
CERTIFICATION	CE & ROHS Approved